SY215C

SY215C 22.6 ton excavator features customized engine, strengthened components, high operating efficiency, low fuel consumption, easy maintenance and comfort cabin.

- Innovative controller with faster consumption and more accuracy reduces the response time of hydraulic elements, lowers the internal power loss of the system and increases the operating output power.
- The positive flow controlled by hydraulic system considerably reduces fuel consumption. Advanced computer dynamic control technology provides a real-time match between engine power and main pump power. Four power modes maximize fuel economy.



SY215e.9/

SY215C


- OPERATING WEIGHT: 21900kg
- ENGINE MODEL:
 Mitsubishi 6D34-TL
- WARRANTY:





SY215C DIMENSIONS & SPECIFICATIONS

	OVERALL DIMENSIONS		
А	Transport Length	9680 mm	
В	Transport Width	2980 mm	
С	Transport Height	3440 mm	
D	Upper Width	2875 mm	
F	Cab Height	3075 mm	
G	Tail Swing Radius	2900 mm	
Н	Min. Ground Clearance	440 mm	
WORKING RANGE			
	WORKING RANGE		
а	WORKING RANGE Maximum Digging Height	9600 mm	
a b		9600 mm 6730 mm	
	Maximum Digging Height		
b	Maximum Digging Height Maximum Dumping Height	6730 mm	
b c	Maximum Digging Height Maximum Dumping Height Maximum Digging Depth Maximum Vertical Digging	6730 mm 6600 mm	
b c d	Maximum Digging Height Maximum Dumping Height Maximum Digging Depth Maximum Vertical Digging Depth	6730 mm 6600 mm 6255 mm	

MACHINE PARAMETERS			
Operating Weight	21900 kg		
Engine Type	Mitsubishi 6D34-TL		
Engine Max Power (Gross)	114/2050 kW/rpm		
Engine Max Torque	590/1400 Nm/rpm		
Engine Displacement	5.86L		
Emission Standard	Tier 2		
Swing Speed	llrpm		
Travel Speed	5.4/3.3km/h		
Fuel Tank Capacity	340 L		
Hydraulic Tank Capacity	239 L		
Engine Oil Capacity	22 L		
Ground Pressure	47.4kPa		
Gradeability	70%/35°		
Bucket Digging Force	138kN		
Arm Digging Force	103kN		
Tractive Force	248kN		
Bucket Capacity	0.93m ³		
Boom Length	5.7m		
Arm Length	2.9m		
Track Gauge	2380mm		
Track Length	4250mm		







NY

Not all products are available in all markets. Under our policy of continuous improvement, Sany reserve the right to change specifications and design without prior notice. The illustrations do not necessarily show the standard version of the machine.



21 EFFICIENT DRIVE, TRUGANINA VIC 3029 PHONE 1300 888 316 WWW.SANYAUSTRALIA.COM.AU